



Motor Oil SL 10W-40

Product Code: 7606

Motor Oil SL 10W-40 is an universal high performance fuel saving semi synthetic oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

Motor Oil SL 10W-40 is formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

Motor Oil SL 10W-40 exceeds the following performance criteria:

Approved	MB-Approval 229.1	VW 501.01/505.00
Exceeds	ACEA A3/B3	API SL/CF

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	10W-40
Density @15°C	kg/m ³	ASTM D4052	868
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	96
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	14.2
Viscosity Index		ASTM D2270	150
Viscosity CCS @-25°, max.	cP	ASTM D5293	7000
Flash Point COC, min	°C	ASTM D92	201
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM D2896	8.0
Sulphated Ash	%wt	ASTM D874	0.95

Date Issued: 25-08-2015	Supersedes: 23-03-2012	Revision Nr.: 1
-------------------------	------------------------	-----------------